



# SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:  
US OSHA Hazard Communication Standard (29 CFR 1910.1200) and Canada WHMIS  
2015 which includes the amended Hazardous Products Act (HPA) and the Hazardous  
Products Regulation (HPR)

Revision Date 01-Oct-2024

Version 1

## 1. Identification

### Product identifier

**Product Name** 3H AVIATION FORM-A-GASKET #3 SEALANT .25PT

### Other means of identification

**Product Code** 80019

**UN number or ID number** UN1866

**Synonyms** CAN Item Number 58931

### Recommended use of the chemical and restrictions on use

**Recommended Use** Sealant

**Restrictions on use** No information available

### Details of the supplier of the safety data sheet

#### Manufacturer Address

ITW Permatex, Inc.  
6875 Parkland Blvd.  
Solon, Ohio 44139 USA  
Telephone: 1-87-Permatex  
(866) 732-9502

#### May Also Be Distributed by:

ITW Permatex Canada  
101-2360 Bristol Circle  
Oakville, ON Canada L6H 6M5  
Telephone: (800) 924-6994

**E-mail address** mail@permatex.com

### Emergency telephone number

**24 Hour Emergency Phone Number** Chem-Tel: 800-255-3924  
International Emergency:  
00+1+ 813-248-0585  
Contract Number: MIS0003453

**24-hour emergency phone number** No information available

## 2. Hazard(s) identification

### Classification

Flammable liquids	Category 2
Carcinogenicity	Category 1B

### Label elements

Contains MAGNESIUM SILICATE; METHYL ISOBUTYL KETONE



**Danger**

**Hazard statements**

Highly flammable liquid and vapor.  
May cause cancer.

**Precautionary Statements - Prevention**

Obtain special instructions before use.  
Do not handle until all safety precautions have been read and understood.  
Use personal protective equipment as required.  
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
Keep container tightly closed.  
Ground and bond container and receiving equipment.  
Use only non-sparking tools.  
Take action to prevent static discharges.  
Use explosion-proof electrical, ventilating, lighting and other equipment.

**Precautionary Statements - Response**

IF exposed or concerned: Get medical advice/attention.

**Skin**

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water and then shower.

**Fire**

In case of fire: Use CO2, dry chemical, or foam for extinction.

**Precautionary Statements - Storage**

Store locked up.  
Store in a well-ventilated place. Keep cool.

**Precautionary Statements - Disposal**

Dispose of contents and container to an approved waste disposal plant.

17.80675 % of the mixture consists of ingredient(s) of unknown acute oral toxicity.  
34.12275 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity.  
59.49965 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas).  
57.45505 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor).  
43.18365 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist).

**Other Information**

May be harmful if swallowed. May be harmful in contact with skin. Toxic to aquatic life. Harmful to aquatic life with long lasting effects.

### 3. Composition/information on ingredients

**Substance**

Not applicable.

**Mixture**

**Synonyms**

CAN Item Number 58931.

Chemical name	CAS No.	Weight-%	Hazardous Material Information Review	Date HMIRA filed and date exemption
---------------	---------	----------	------------------------------------------	----------------------------------------

			Act registry number (HMIRA registry #)	granted (if applicable)
FUMARATED RESIN	65997-04-8	10-30%	-	-
MAGNESIUM SILICATE	14807-96-6	10-30%	-	-
ETHANOL	64-17-5	10-30%	-	-
2-PROPANOL	67-63-0	1-5%	-	-
METHANOL	67-56-1	0.1-1%	-	-
METHYL ISOBUTYL KETONE	108-10-1	0.1-1%	-	-

#### 4. First-aid measures

##### Description of first aid measures

General advice	IF exposed or concerned: Get medical advice/attention.
Inhalation	Remove to fresh air.
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area.
Skin contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.
Ingestion	Rinse mouth.
Self-protection of the first aider	Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Use personal protective equipment as required. See section 8 for more information.

##### Most important symptoms and effects, both acute and delayed

Symptoms	No information available.
Effects of Exposure	May cause cancer.

##### Indication of any immediate medical attention and special treatment needed

Note to physicians	Treat symptomatically.
--------------------	------------------------

#### 5. Fire-fighting measures

Suitable Extinguishing Media	Dry chemical. Carbon dioxide (CO2). Water spray. Alcohol resistant foam.
Small Fire	In case of fire, use water spray, foam, dry chemical, or CO2.
Large Fire	In case of fire, use water spray, foam, dry chemical, or CO2.
Unsuitable extinguishing media	Do not scatter spilled material with high pressure water streams.
Specific hazards arising from the chemical	Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Hazardous combustion products	No information available.
Explosion data	
Sensitivity to mechanical impact	None.
Sensitivity to static discharge	Yes.

**Special protective equipment and precautions for fire-fighters** Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

## 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

**Personal precautions** Evacuate personnel to safe areas. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Do not touch or walk through spilled material.

**Other information** Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

### Methods and material for containment and cleaning up

**Methods for containment** Stop leak if you can do it without risk. Do not touch or walk through spilled material. A vapor suppressing foam may be used to reduce vapors. Dike far ahead of spill to collect runoff water. Keep out of drains, sewers, ditches and waterways. Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal.

**Methods for cleaning up** Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers.

**Prevention of secondary hazards** Clean contaminated objects and areas thoroughly observing environmental regulations.

## 7. Handling and storage

### Precautions for safe handling

**Advice on safe handling** Use personal protection equipment. Avoid breathing vapors or mists. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing.

### Conditions for safe storage, including any incompatibilities

**Storage Conditions** Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations.

## 8. Exposure controls/personal protection

### Control parameters Exposure Limits

Chemical name	ACGIH TLV	OSHA PEL	NIOSH
MAGNESIUM SILICATE 14807-96-6	TWA: 2 mg/m <sup>3</sup> particulate matter containing no asbestos and <1% crystalline silica, respirable particulate matter	TWA: 20 mppcf if 1% Quartz or more, use Quartz limit (vacated) TWA: 2 mg/m <sup>3</sup> respirable dust <1% Crystalline silica, containing no Asbestos TWA: 20 mppcf if 1% Quartz or more, use Quartz limit	IDLH: 1000 mg/m <sup>3</sup> TWA: 2 mg/m <sup>3</sup> containing no Asbestos and <1% Quartz respirable dust
ETHANOL 64-17-5	STEL: 1000 ppm	TWA: 1000 ppm TWA: 1900 mg/m <sup>3</sup> (vacated) TWA: 1000 ppm (vacated) TWA: 1900 mg/m <sup>3</sup>	IDLH: 3300 ppm TWA: 1000 ppm TWA: 1900 mg/m <sup>3</sup>
2-PROPANOL 67-63-0	TWA: 200 ppm STEL: 400 ppm	TWA: 400 ppm TWA: 980 mg/m <sup>3</sup> (vacated) TWA: 400 ppm (vacated) TWA: 980 mg/m <sup>3</sup> (vacated) STEL: 500 ppm (vacated) STEL: 1225 mg/m <sup>3</sup>	IDLH: 2000 ppm TWA: 400 ppm TWA: 980 mg/m <sup>3</sup> STEL: 500 ppm STEL: 1225 mg/m <sup>3</sup>
METHANOL 67-56-1	TWA: 200 ppm STEL: 250 ppm Sk*	TWA: 200 ppm TWA: 260 mg/m <sup>3</sup> (vacated) TWA: 200 ppm (vacated) TWA: 260 mg/m <sup>3</sup> (vacated) STEL: 250 ppm (vacated) STEL: 325 mg/m <sup>3</sup> (vacated) Sk*	IDLH: 6000 ppm TWA: 200 ppm TWA: 260 mg/m <sup>3</sup> STEL: 250 ppm STEL: 325 mg/m <sup>3</sup>
METHYL ISOBUTYL KETONE 108-10-1	TWA: 20 ppm STEL: 75 ppm	TWA: 100 ppm TWA: 410 mg/m <sup>3</sup> (vacated) TWA: 50 ppm (vacated) TWA: 205 mg/m <sup>3</sup> (vacated) STEL: 75 ppm (vacated) STEL: 300 mg/m <sup>3</sup>	IDLH: 500 ppm TWA: 50 ppm TWA: 205 mg/m <sup>3</sup> STEL: 75 ppm STEL: 300 mg/m <sup>3</sup>

Chemical name	Alberta	British Columbia	Ontario	Quebec
MAGNESIUM SILICATE 14807-96-6	TWA: 2 mg/m <sup>3</sup>	TWA: 2 mg/m <sup>3</sup>	TWA: 2 mg/m <sup>3</sup>	TWA: 2 mg/m <sup>3</sup>
ETHANOL 64-17-5	TWA: 1000 ppm TWA: 1880 mg/m <sup>3</sup>	STEL: 1000 ppm	STEL: 1000 ppm	STEL: 1000 ppm
2-PROPANOL 67-63-0	TWA: 200 ppm TWA: 492 mg/m <sup>3</sup> STEL: 400 ppm STEL: 984 mg/m <sup>3</sup>	TWA: 200 ppm STEL: 400 ppm	TWA: 200 ppm STEL: 400 ppm	TWA: 200 ppm STEL: 400 ppm
METHANOL 67-56-1	TWA: 200 ppm TWA: 262 mg/m <sup>3</sup> STEL: 250 ppm STEL: 328 mg/m <sup>3</sup> Sk*	TWA: 200 ppm STEL: 250 ppm Sk*	TWA: 200 ppm STEL: 250 ppm Sk*	TWA: 200 ppm TWA: 262 mg/m <sup>3</sup> STEL: 250 ppm STEL: 328 mg/m <sup>3</sup> Skin
METHYL ISOBUTYL KETONE 108-10-1	TWA: 50 ppm TWA: 205 mg/m <sup>3</sup> STEL: 75 ppm STEL: 307 mg/m <sup>3</sup>	TWA: 20 ppm STEL: 75 ppm	TWA: 20 ppm STEL: 75 ppm	TWA: 20 ppm STEL: 75 ppm

Chemical name	Manitoba	New Brunswick	Newfoundland and Labrador	Nova Scotia
MAGNESIUM SILICATE	TWA: 2 mg/m <sup>3</sup>	TWA: 2 mg/m <sup>3</sup>	TWA: 2 mg/m <sup>3</sup>	TWA: 2 mg/m <sup>3</sup>
ETHANOL	STEL: 1000 ppm	STEL: 1000 ppm	STEL: 1000 ppm	STEL: 1000 ppm
2-PROPANOL	TWA: 200 ppm	TWA: 200 ppm	TWA: 200 ppm	TWA: 200 ppm

Chemical name	Manitoba	New Brunswick	Newfoundland and Labrador	Nova Scotia
	STEL: 400 ppm	STEL: 400 ppm	STEL: 400 ppm	STEL: 400 ppm
METHANOL	TWA: 200 ppm STEL: 250 ppm Sk*	TWA: 200 ppm STEL: 250 ppm Sk*	TWA: 200 ppm STEL: 250 ppm Sk*	TWA: 200 ppm STEL: 250 ppm Sk*
METHYL ISOBUTYL KETONE	TWA: 20 ppm STEL: 75 ppm	TWA: 20 ppm STEL: 75 ppm	TWA: 20 ppm STEL: 75 ppm	TWA: 20 ppm STEL: 75 ppm

Chemical name	Nunavut	Prince Edward Island	Saskatchewan	Yukon
MAGNESIUM SILICATE	TWA: 2 mg/m <sup>3</sup>	TWA: 2 mg/m <sup>3</sup>	TWA: 2 mg/m <sup>3</sup>	TWA: 20 mppcf
ETHANOL	TWA: 1000 ppm STEL: 1250 ppm	STEL: 1000 ppm	TWA: 1000 ppm STEL: 1250 ppm	TWA: 1000 ppm TWA: 1900 mg/m <sup>3</sup> STEL: 1000 ppm STEL: 1900 mg/m <sup>3</sup>
2-PROPANOL	TWA: 200 ppm STEL: 400 ppm	TWA: 200 ppm STEL: 400 ppm	TWA: 200 ppm STEL: 400 ppm	TWA: 400 ppm TWA: 980 mg/m <sup>3</sup> STEL: 500 ppm STEL: 1225 mg/m <sup>3</sup> Sk*
METHANOL	TWA: 200 ppm STEL: 250 ppm Sk*	TWA: 200 ppm STEL: 250 ppm	TWA: 200 ppm STEL: 250 ppm Skin	TWA: 200 ppm TWA: 260 mg/m <sup>3</sup> STEL: 250 ppm STEL: 310 mg/m <sup>3</sup> Sk*
METHYL ISOBUTYL KETONE	TWA: 50 ppm STEL: 75 ppm	TWA: 20 ppm STEL: 75 ppm	TWA: 50 ppm STEL: 75 ppm	TWA: 100 ppm TWA: 410 mg/m <sup>3</sup> STEL: 125 ppm STEL: 510 mg/m <sup>3</sup> Sk*

### Biological occupational exposure limits

Chemical name	ACGIH
2-PROPANOL 67-63-0	40 mg/L - urine (Acetone) - end of shift at end of workweek
METHANOL 67-56-1	15 mg/L - urine (Methanol) - end of shift
METHYL ISOBUTYL KETONE 108-10-1	1 mg/L - urine (MIBK) - end of shift

### Appropriate engineering controls

**Engineering controls**                      Showers  
Eyewash stations  
Ventilation systems.

### Individual protection measures, such as personal protective equipment

**Eye/face protection**                      Tight sealing safety goggles.

**Hand protection**                              Wear suitable gloves. Impervious gloves.

**Skin and body protection**                      Wear suitable protective clothing. Long sleeved clothing. Chemical resistant apron.

Antistatic boots.

**Respiratory protection**

Appropriate respiratory protection should be selected and used according to the chemical nature, hazards and use of this product and safety requirements of the local jurisdiction. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

**General hygiene considerations**

Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product.

**Thermal hazards**

No information available.

**9. Physical and chemical properties****Information on basic physical and chemical properties**

<b>Physical state</b>	Liquid
<b>Appearance</b>	No information available
<b>Color</b>	Brown
<b>Odor</b>	No information available
<b>Odor threshold</b>	No information available

**Property****Values****Remarks • Method**

<b>pH</b>	No data available	
<b>Melting point / freezing point</b>	No data available	<b>Boiling point / boiling range</b> 82 °C / 179.6 °F
		<b>Flash point</b> 16 °C / 60.8 °F
		<b>Evaporation rate</b> 7.7
Ether = 1		<b>Flammability (solid, gas)</b> No data available
<b>Flammability Limit in Air</b>		<b>Upper flammability limit:</b> 12.0%
		<b>Lower flammability limit:</b> 2.0%
		<b>Vapor pressure</b> 33 mm Hg
		<b>Vapor density</b> 2.07
Air = 1		<b>Relative density</b> 1.090-1.114
		<b>Water solubility</b> No data available
		Partially soluble
<b>Partition coefficient</b>	No Data Available	<b>Solubility(ies)</b> No Data Available
<b>Decomposition temperature</b>	No data available	<b>Autoignition temperature</b> No data available
<b>Dynamic viscosity</b>	No data available	<b>Kinematic viscosity</b> No Data Available
<b>Other information</b>		
<b>Explosive properties</b>	No information available	
<b>Oxidizing properties</b>	No information available	
<b>Softening point</b>	No information available	
<b>Molecular weight</b>	No information available	
<b>VOC content</b>	19.4216	
<b>Density</b>	No information available	
<b>Bulk density</b>	No information available	

**10. Stability and reactivity****Reactivity**

No information available.

Chemical stability	Stable under normal conditions.
Possibility of hazardous reactions	None under normal processing.
Hazardous polymerization	No information available.
Conditions to avoid	Heat, flames and sparks.
Incompatible materials	None known based on information supplied.
Hazardous decomposition products	Carbon oxides. Aldehydes. Carboxylic acids.

## 11. Toxicological information

### Information on likely routes of exposure

#### Product Information

Inhalation	Specific test data for the substance or mixture is not available.
Eye contact	Specific test data for the substance or mixture is not available.
Skin contact	May be harmful in contact with skin.
Ingestion	Specific test data for the substance or mixture is not available.

### Symptoms related to the physical, chemical and toxicological characteristics

Symptoms	No information available.
----------	---------------------------

### Acute toxicity

#### Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)	3,550.10 mg/kg
ATEmix (dermal)	4,466.50 mg/kg
ATEmix (inhalation-gas)	99,999.00 ppm
ATEmix (inhalation-vapor)	626.3384 mg/l
ATEmix (inhalation-dust/mist)	30.10 mg/l

17.80675 % of the mixture consists of ingredient(s) of unknown acute oral toxicity  
34.12275 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity  
59.49965 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas)  
57.45505 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor)  
43.18365 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist)

#### Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
FUMARATED RESIN 65997-04-8	> 2000 mg/kg ( Rat )	= 2000 mg/kg ( Rat )	-
ETHANOL 64-17-5	= 7060 mg/kg ( Rat )	-	= 116.9 mg/L ( Rat ) 4 h = 133.8 mg/L ( Rat ) 4 h
2-PROPANOL 67-63-0	5050 mg/kg	12800 mg/kg	> 10000 ppm ( Rat ) 6 h
METHANOL 67-56-1	= 6200 mg/kg ( Rat )	= 15840 mg/kg ( Rabbit )	= 22500 ppm ( Rat ) 8 h
METHYL ISOBUTYL KETONE 108-10-1	= 2080 mg/kg ( Rat )	= 3000 mg/kg ( Rabbit )	2000 - 4000 ppm ( Rat ) 4 h



**Delayed and immediate effects as well as chronic effects from short and long-term exposure****Skin corrosion/irritation** No information available.**Serious eye damage/eye irritation** No information available.**Respiratory or skin sensitization** No information available.**Germ cell mutagenicity** No information available.**Carcinogenicity** Contains a known or suspected carcinogen. Classification based on data available for ingredients. May cause cancer.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
MAGNESIUM SILICATE 14807-96-6	-	Group 2A	-	X
ETHANOL 64-17-5	A3	Group 1	Known	X
METHYL ISOBUTYL KETONE 108-10-1	A3	Group 2B	-	X

**Legend****ACGIH (American Conference of Governmental Industrial Hygienists)**

A3 - Animal Carcinogen

**IARC (International Agency for Research on Cancer)**

Group 1 - Carcinogenic to Humans

Group 2A - Probably Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

**NTP (National Toxicology Program)**

Known - Known Carcinogen

**Occupational Safety and Health Administration of the US Department of Labor**

X - Present

**Reproductive toxicity** No information available.**STOT - single exposure** No information available.**STOT - repeated exposure** No information available.**Aspiration hazard** No information available.**12. Ecological information****Ecotoxicity** Toxic to aquatic life. Harmful to aquatic life with long lasting effects.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
FUMARATED RESIN 65997-04-8	-	LC50: =3.2mg/L (96h, Brachydanio rerio)	-	-
MAGNESIUM SILICATE	-	LC50: >100g/L (96h,	-	-

14807-96-6 ETHANOL 64-17-5	-	Brachydanio rerio) LC50: 12.0 - 16.0mL/L (96h, Oncorhynchus mykiss) LC50: >100mg/L (96h, Pimephales promelas) LC50: 13400 - 15100mg/L (96h, Pimephales promelas)	-	LC50: 9268 - 14221mg/L (48h, Daphnia magna) EC50: =2mg/L (48h, Daphnia magna)
2-PROPANOL 67-63-0	EC50: >1000mg/L (96h, Desmodesmus subspicatus) EC50: >1000mg/L (72h, Desmodesmus subspicatus)	LC50: =9640mg/L (96h, Pimephales promelas) LC50: =11130mg/L (96h, Pimephales promelas) LC50: >1400000µg/L (96h, Lepomis macrochirus)	-	EC50: =13299mg/L (48h, Daphnia magna)
METHANOL 67-56-1	-	LC50: =28200mg/L (96h, Pimephales promelas) LC50: >100mg/L (96h, Pimephales promelas) LC50: 19500 - 20700mg/L (96h, Oncorhynchus mykiss) LC50: 18 - 20mL/L (96h, Oncorhynchus mykiss) LC50: 13500 - 17600mg/L (96h, Lepomis macrochirus)	-	-
METHYL ISOBUTYL KETONE 108-10-1	EC50: =400mg/L (96h, Pseudokirchneriella subcapitata)	LC50: 496 - 514mg/L (96h, Pimephales promelas)	-	EC50: =170mg/L (48h, Daphnia magna)

**Persistence and degradability** No information available.

#### Bioaccumulation

##### Component Information

Chemical name	Partition coefficient
FUMARATED RESIN 65997-04-8	7
ETHANOL 64-17-5	-0.35
2-PROPANOL 67-63-0	0.05
METHANOL 67-56-1	-0.77
METHYL ISOBUTYL KETONE 108-10-1	1.9

**Other adverse effects** No information available.

### 13. Disposal considerations

#### Waste treatment methods

<b>Waste from residues/unused products</b>	Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.
<b>Contaminated packaging</b>	Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.
<b>US EPA Waste Number</b>	Waste designations and classifications should be determined by the end user based on the application for which the product was used.

## 14. Transport information

### DOT

UN number or ID number	UN1866
Proper shipping name	Resin solution Limited Quantity (LQ)
Transport hazard class(es)	3
Packing group	II
DOT Marine Pollutant	NP
Marine pollutant	FUMARATED RESIN.
Description	UN1866, Resin solution, 3, II, Limited Quantity (LQ)
Special Provisions	149, B52, IB2, T4, TP1, TP8
Emergency Response Guide Number	127

### TDG

UN number or ID number	UN1866
UN proper shipping name	Resin solution
Transport hazard class(es)	3
Packing group	II
Description	UN1866, Resin solution, 3, II

### MEX

UN number or ID number	UN1866
UN proper shipping name	Resin solution
Transport hazard class(es)	3
Packing group	II
Description	UN1866, Resin solution, 3, II

### ICAO (air)

UN number or ID number	UN1866
UN proper shipping name	Resin solution
Transport hazard class(es)	3
Packing group	II
Description	UN1866, Resin solution, 3, II
Special Provisions	A3

### IATA

UN number or ID number	UN1866
UN proper shipping name	Resin solution
Transport hazard class(es)	3
Packing group	II
ERG Code	3L
Special Provisions	A3
Description	UN1866, Resin solution, 3, II

### IMDG

UN number or ID number	UN1866
UN proper shipping name	Resin solution
Transport hazard class(es)	3

Packing group II  
EmS-No. F-E, S-E  
Description UN1866, Resin solution, 3, II, (16°C c.c.)

## 15. Regulatory information

### Safety, health and environmental regulations/legislation specific for the substance or mixture

#### International Regulations

The Montreal Protocol on Substances that Deplete the Ozone Layer Not applicable

The Stockholm Convention on Persistent Organic Pollutants Not applicable

The Rotterdam Convention Not applicable

#### International Inventories

TSCA	Complies
DSL/NDSL	Complies
EINECS/ELINCS	Complies
ENCS	Does not comply
IECSC	Complies
KECI	Complies
PICCS	Complies
AICS	Complies
NZIoC	Complies

#### Legend:

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory

**DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List

**EINECS/ELINCS** - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances

**IECSC** - China Inventory of Existing Chemical Substances

**KECL** - Korean Existing Chemicals Inventory

**PICCS** - Philippines Inventory of Chemicals and Chemical Substances

**AICS** - Australian Inventory of Chemical Substances

**NZIoC** - New Zealand Inventory of Chemicals

#### US Federal Regulations

##### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Chemical name	SARA 313 - Threshold Values %
2-PROPANOL - 67-63-0	1.0
METHYL ISOBUTYL KETONE - 108-10-1	0.1

##### **SARA 311/312 Hazard Categories**

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

##### **CWA (Clean Water Act)**

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

##### **CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302).

Chemical name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	Reportable Quantity (RQ)
METHANOL 67-56-1	5000 lb	-	RQ 5000 lb final RQ RQ 2270 kg final RQ
METHYL ISOBUTYL KETONE 108-10-1	5000 lb	-	RQ 5000 lb final RQ RQ 2270 kg final RQ

### US State Regulations

#### California Proposition 65

This product contains the following Proposition 65 chemicals:

Chemical name	California Proposition 65
ETHANOL - 64-17-5	*Developmental (in alcoholic beverages)
METHANOL - 67-56-1	Developmental
METHYL ISOBUTYL KETONE - 108-10-1	Carcinogen Developmental

Ethanol has been shown to be carcinogenic in long-term studies only when consumed as alcoholic beverage Ethanol has been shown to be a reproductive toxin only when consumed as an alcoholic beverage

### U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
MAGNESIUM SILICATE 14807-96-6	X	X	X
WATER 7732-18-5	-	-	X
METHYL ISOBUTYL KETONE 108-10-1	X	X	X

### U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

## 16. Other information

**NFPA** Health hazards 1 Flammability 3 Instability 0 Special hazards -  
**HMIS** Health hazards \* Flammability 3 Physical hazards 0 Personal protection X  
Chronic Hazard Star Legend \* = Chronic Health Hazard

### Key or legend to abbreviations and acronyms used in the safety data sheet

#### Legend

SVHC: Substances of Very High Concern for Authorization:  
PBT: Persistent, Bioaccumulative, and Toxic (PBT) Substances  
vPvB: Very Persistent and very Bioaccumulative (vPvB) Substances  
STOT: Specific Target Organ Toxicity  
ATE: Acute Toxicity Estimate  
LC50: 50% Lethal Concentration  
LD50: 50% Lethal Dose

#### Legend Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA TWA (time-weighted average) STEL STEL (Short Term Exposure Limit)  
Ceiling Maximum limit value \* Skin designation  
+ Sensitizers

### Key literature references and sources for data used to compile the SDS

Agency for Toxic Substances and Disease Registry (ATSDR)  
U.S. Environmental Protection Agency ChemView Database  
European Food Safety Authority (EFSA)  
Environmental Protection Agency  
Acute Exposure Guideline Level(s) (AEGL(s))  
U.S. Environmental Protection Agency Federal Insecticide, Fungicide, and Rodenticide Act  
U.S. Environmental Protection Agency High Production Volume Chemicals  
Food Research Journal  
Hazardous Substance Database  
International Uniform Chemical Information Database (IUCLID)  
National Institute of Technology and Evaluation (NITE)  
Australia National Industrial Chemicals Notification and Assessment Scheme (NICNAS)  
NIOSH (National Institute for Occupational Safety and Health)  
National Library of Medicine's ChemID Plus (NLM CIP)  
National Library of Medicine's PubMed database (NLM PUBMED)  
U.S. National Toxicology Program (NTP)  
New Zealand's Chemical Classification and Information Database (CCID)  
Organization for Economic Co-operation and Development Environment, Health, and Safety Publications  
Organization for Economic Co-operation and Development High Production Volume Chemicals Program  
Organization for Economic Co-operation and Development Screening Information Data Set  
World Health Organization

**Revision Date** 01-Oct-2024

**Revision Note** No information available.

**Disclaimer**

**The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.**