

SAFETY DATA SHEET

Print Date: 04-Nov-2021 Revision Date: 04-Nov-2021 Issuing Date: 04-Nov-2021

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product Code: 03174YVP-1

Product Name: METAL PRETREATMENT WASH PRIMER, MIL-C-8514C, AMEND 1, HMS15-1098E REV: (F), PART A

Hentzen Coatings, Inc.

Company Phone Number: 1-414-353-4200

6937 West Mill Road, Milwaukee, WI 53218-1225

Emergency telephone number ChemTrec 1-800-424-9300

Recommended use of the chemical and restrictions on use Industrial paint (Paint or Paint-Related), Restricted to

professional users

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity - Oral	Category 4
Skin Corrosion/Irritation	Category 2
Serious eye damage/eye irritation	Category 1
Skin sensitization	Category 1
Carcinogenicity	Category 1A
Specific target organ toxicity (single exposure)	Category 1
Flammable Liquids	Category 2


Label Elements

Emergency Overview

DANGER

Hazard Statements

Harmful if swallowed Causes skin irritation Causes serious eye damage May cause an allergic skin reaction May cause cancer Causes damage to organs Highly flammable liquid and vapor



Appearance Opaque

Physical state Liquid

Odor Solvent

Precautionary Statements - Prevention

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Wash face, hands and any exposeo skin thoroughly after handling

Revision Date: 04-Nov-2021

Do not eat, drink or smoke when using this product Contaminated work clothing should not be allowed out of the workplace Wear protective gloves Do not breathe dust/fume/gas/mist/vapors/spray Keep away from heat/sparks/open flames/hot surfaces. - No smoking Keep container tightly closed Ground/Bond container and receiving equipment Use explosion-proof electrical/ ventilating/ lighting/ equipment Use only non-sparking tools Take precautionary measures against static discharge

Precautionary Statements - Response

IF exposed: Call a POISON CENTER or doctor/physician

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

Immediately call a POISON CENTER or doctor/physician

If skin irritation or rash occurs: Get medical advice/attention IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

Wash contaminated clothing before reuse

IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell

Rinse mouth

In case of fire: Use CO2, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store in a well-ventilated place. Keep cool Store in accordance with local regulations

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

- Other information

 Toxic to aquatic life with long lasting effects
- · Toxic to aquatic life

3. COMPOSITION/INFORMATION ON INGREDIENTS

Contains a known or suspected carcinogen

This product contains substances regulated as hazardous air pollutants (HAPS) under Section 112 of the Clean Air Act Amendments of 1990. See Section 15 for list of HAPS.

Chemical Name	CAS No	Weight-%	ACGIH	OSHA
ETHYL ALCOHOL	64-17-5	50% - 60%	STEL: 1000 ppm	TWA: 1000 ppm TWA: 1900 mg/m ³
BUTYL ALCOHOL	71-36-3	10% - 20%	TWA: 20 ppm	TWA: 100 ppm TWA: 300 mg/m ³
ZINC TETRAOXYCHROMATE	49663-84-5	5% - 10%	N/A	TWA: 5 µg/m³ Ceiling: 0.1 mg/m³ CrO3 applies to any operations or sectors for which the Hexavalent Chromium standard [29 CFR 1910.1026] is stayed or is otherwise not in effect
ISOPROPYL ALCOHOL	67-63-0	1% - 5%	STEL: 400 ppm TWA: 200 ppm	TWA: 400 ppm TWA: 980 mg/m ³
METHANOL	67-56-1	1% - 5%	STEL: 250 ppm TWA: 200 ppm S*	TWA: 200 ppm TWA: 260 mg/m ³

Revision Date: 04-Nov-2021

4. FIRST AID MEASURES

First Aid Measures

General advice Show this safety data sheet to the doctor in attendance. If symptoms persist, call a

physician.

Eye Contact Immediately flush eyes with water for at least 15 minutes. Get medical attention. If easy to

do, remove contact lenses. Keep eye wide open while rinsing. Call a physician immediately.

If symptoms persist, call a physician.

Skin Contact Immediate medical attention is not required. Wash off immediately with soap and plenty of

water while removing all contaminated clothes and shoes. If skin irritation persists, call a

physician.

Inhalation Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Remove to

fresh air. If not breathing, give artificial respiration. Immediate medical attention is not required. Move to fresh air in case of accidental inhalation of vapors. If symptoms persist,

call a physician.

Ingestion Do NOT induce vomiting. Drink plenty of water. Never give anything by mouth to an

unconscious person. Call a physician or poison control center immediately. Clean mouth

with water and afterwards drink plenty of water. Consult a physician if necessary.

Self-protection of the first aider Remove all sources of ignition. Use personal protective equipment as required.

Most important symptoms and effects, both acute and delayed

Most Important Symptoms and

Effects

No information available.

Indication of any immediate medical attention and special treatment needed

Notes to physician

Treat symptomatically. May cause sensitization of susceptible persons.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable Extinguishing Media No information available.

Specific hazards arising from the chemical

Flammable. Thermal decomposition can lead to release of irritating gases and vapors. In the event of fire and/or explosion do not breathe fumes. May cause sensitization by inhalation and skin contact.

Explosion Data

Sensitivity to Mechanical Impact no data available.

Sensitivity to Static Discharge Yes.

Protective equipment and precautions for firefighters

Wear self contained breathing apparatus for fire fighting if necessary.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions Remove all sources of ignition. Evacuate personnel to safe areas. Ensure adequate

ventilation. Use personal protective equipment as required. Keep people away from and

upwind of spill/leak. Avoid breathing vapors or mists. Ventilate the area.

Revision Date: 04-Nov-2021

Environmental Precautions

Environmental Precautions

Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Do not flush into surface water or sanitary sewer system. Vapors are heavier than air, spread along floors and form explosive mixtures with air.

Methods and materials for containment and cleaning up

Methods for Containment

Prevent further leakage or spillage if safe to do so. Dike far ahead of liquid spill for later disposal.

Methods for Cleaning Up

Dam up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Pick up and transfer to properly labeled containers. Soak up with inert

absorbent material.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling

Ensure adequate ventilation. Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges. Use explosion-proof electrical (ventilation and lighting) equipment. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use with local exhaust ventilation. Wear protective gloves/protective clothing/eye protection/face protection. Do not breathe vapor or mist. To dissipate static electricity during transfer, ground drum and connect to receiving container with bonding strap. Use only non-sparking tools.

Conditions for safe storage, including any incompatibilities

Storage Conditions

Keep tightly closed in a dry and cool place. Keep in properly labeled containers. Keep containers tightly closed in a cool, well-ventilated place. Keep away from heat, sparks and

flame.

Incompatible Products

None known based on information supplied.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH	OSHA	NIOSH IDLH
ETHYL ALCOHOL	STEL: 1000 ppm	TWA: 1000 ppm	IDLH: 3300 ppm
64-17-5		TWA: 1900 mg/m ³	TWA: 1000 ppm
			TWA: 1900 mg/m ³
BUTYL ALCOHOL	TWA: 20 ppm	TWA: 100 ppm	IDLH: 1400 ppm
71-36-3		TWA: 300 mg/m ³	Ceiling: 50 ppm
			Ceiling: 150 mg/m ³
ZINC TETRAOXYCHROMATE	N/A	TWA: 5 μg/m³	IDLH: 15 mg/m ³ Cr(VI)
49663-84-5		Ceiling: 0.1 mg/m ³ CrO3 applies to	TWA: 0.0002 mg/m ³ Cr
1		any operations or sectors for which	
		the Hexavalent Chromium standard	
		[29 CFR 1910.1026] is stayed or is	
		otherwise not in effect	
ISOPROPYL ALCOHOL	STEL: 400 ppm	TWA: 400 ppm	IDLH: 2000 ppm
67-63-0	TWA: 200 ppm	TWA: 980 mg/m ³	TWA: 400 ppm
		17	TWA: 980 mg/m ³
			STEL: 500 ppm
			STEL: 1225 mg/m ³
METHANOL	STEL: 250 ppm	TWA: 200 ppm	IDLH: 6000 ppm
67-56-1	TWA: 200 ppm	TWA: 260 mg/m ³	TWA: 200 ppm

Revision Date: 04-Nov-2021

No data available

7.37

5.95

	S*	TWA: 260 mg/m ³ STEL: 250 ppm STEL: 325 mg/m ³
--	----	--

NIOSH IDLH: Immediately Dangerous to Life or Health

Exposure controls

Engineering Measures

Showers

Eyewash stations Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/Face Protection

Use personal protective equipment as required.

Skin and Body Protection

Chemical resistant apron.

Respiratory Protection

If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be

provided in accordance with current local regulations.

Hygiene Measures

Do not eat, drink or smoke when using this product. Regular cleaning of equipment, work

area and clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state Liquid **Appearance** Opaque Solvent. No data available **Odor Threshold** Odor рΗ No data available Flash Point 55 °F / 13 °C 145 °F / 63 °C Decomposition temperature No data available **Boiling Point** Freezing Point No data available Melting Point / Melting Range No data available Vapor Pressure @20°C (kPa) No data available Partition coefficient: No data available Vapor Density No data available Density No data available 0.88 **Bulk density** No data available Specific Gravity

Evaporation Rate
Dynamic viscosity

No data available
No data available
No data available

Water solubility Weight per Gallon (lbs/gal): EPA VOC (lb/gal)

10.59 %

Flammability Limits in Air

Upper 10.59 % **Lower** 1.84 %

10. STABILITY AND REACTIVITY

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Conditions to Avoid

Extremes of temperature and direct sunlight.

Incompatible Materials

None known based on information supplied.

Hazardous Decomposition Products

None known based on information supplied.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Revision Date: 04-Nov-2021

Product Information

The product has not been tested

Inhalation

There is no data for this product.

Eye Contact

There is no data for this product.

Skin Contact

There is no data for this product.

Ingestion

There is no data for this product.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
ETHYL ALCOHOL 64-17-5	= 7060 mg/kg (Rat)	N/A	= 124.7 mg/L (Rat) 4 h
BUTYL ALCOHOL 71-36-3	= 700 mg/kg (Rat)	= 3402 mg/kg (Rabbit)	> 8000 ppm (Rat) 4 h
SOPROPYL ALCOHOL 67-63-0	= 1870 mg/kg (Rat)	= 4059 mg/kg (Rabbit)	= 72600 mg/m³ (Rat) 4 h
METHANOL 67-56-1	= 6200 mg/kg (Rat)	= 15840 mg/kg (Rabbit)	= 22500 ppm (Rat) 8 h

Information on toxicological effects

Symptoms

No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization

No information available.

MUTAGENIC EFFECTS

No information available.

Carcinogenicity

This product contains one or more substances which are classified by IARC as

carcinogenic to humans (Group I), probably carcinogenic to humans (Group 2A) or possibly

carcinogenic to humans (Group 2B).

Chemical Name	ACGIH	IARC	NTP	OSHA
ETHYL ALCOHOL 64-17-5	A3	Group 1	Known	X
ZINC TETRAOXYCHROMATE 49663-84-5	N/A	Group 1	Known	х
ISOPROPYL ALCOHOL 67-63-0	N/A	Group 3	N/A	X

Legend:

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 3 - Not Classifiable as to Carcinogenicity in Humans

NTP (National Toxicology Program)

Known - Known Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Reproductive Toxicity

Specific target organ systemic toxicity (single exposure)

Specific target organ systemic toxicity (repeated exposure)

Chronic Toxicity

No information available. No information available.

No information available.

Avoid repeated exposure. May cause adverse effects on the bone marrow and

blood-forming system. May cause adverse liver effects. Contains a known or suspected reproductive toxin. Repeated contact may cause allergic reactions in very susceptible persons.

Blood, Central nervous system (CNS), Eyes, Gastrointestinal tract (GI), Kidney, Liver. **Target Organ Effects**

Lungs, Reproductive system, Respiratory system, Skin.

Aspiration hazard

No information available.

Revision Date: 04-Nov-2021

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral)

1618 mg/kg

ATEmix (dermal)

6812 mg/kg

ATEmix (inhalation-dust/mist)

20.2 mg/l

Oral LD50

2673 mg/kg (rat) Estimated

Dermal LD50

15198 mg/kg (rat) Estimated

Inhalation LC50

226788 mg/l (mist) (dust) mg/m3 Estimated

Inhalation LC50

ml/m3 (vapor) Estimated

12. ECOLOGICAL INFORMATION

Ecotoxicity

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to daphnia and other aquatic invertebrates
ETHYL ALCOHOL	N/A	12.0 - 16.0: 96 h Oncorhynchus	9268 - 14221: 48 h Daphnia magna
64-17-5	7555000 OC	mykiss mL/L LC50 static 13400 -	mg/L LC50 2: 48 h Daphnia magna
		15100: 96 h Pimephales promelas	mg/L EC50 Static
		mg/L LC50 flow-through 100: 96 h	
		Pimephales promelas mg/L LC50	
		static	
BUTYL ALCOHOL	500: 72 h Desmodesmus	100000 - 500000: 96 h Lepomis	1897 - 2072: 48 h Daphnia magna
71-36-3		macrochirus µg/L LC50 static 1730 -	
	Desmodesmus subspicatus mg/L	1910: 96 h Pimephales promelas	Daphnia magna mg/L EC50
	EC50	mg/L LC50 static 1740: 96 h	
1		Pimephales promelas mg/L LC50	
		flow-through 1910000: 96 h	
		Pimephales promelas µg/L LC50	
		static	10000 10 h Dh-i
ISOPROPYL ALCOHOL	1000: 72 h Desmodesmus	11130: 96 h Pimephales promelas	13299: 48 h Daphnia magna mg/L
67-63-0	subspicatus mg/L EC50 1000: 96 h		EC50
	Desmodesmus subspicatus mg/L	Pimephales promelas mg/L LC50	
	EC50	flow-through 1400000: 96 h	
		Lepomis macrochirus µg/L LC50	N/A
METHANOL	N/A	13500 - 17600: 96 h Lepomis	IN/A
67-56-1		macrochirus mg/L LC50	
		flow-through 18 - 20: 96 h	
1		Oncorhynchus mykiss mL/L LC50 static 19500 - 20700: 96 h	
		Oncorhynchus mykiss mg/L LC50	
		flow-through 28200: 96 h	
		Pimephales promelas mg/L LC50	
a		flow-through 100: 96 h Pimephales	
		promelas mg/L LC50 static	

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Chemical Name	Partition coefficient
ETHYL ALCOHOL 64-17-5	-0.32
BUTYL ALCOHOL 71-36-3	0.785
ISOPROPYL ALCOHOL 67-63-0	0.05
METHANOL 67-56-1	-0.77

Revision Date: 04-Nov-2021

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Waste treatment methods

This material, as supplied, is a hazardous waste according to federal regulations (40 CFR

261).

US EPA Waste Number

D001

Chemical Name	RCRA - Basis for Listing	RCRA - D Series Wastes
BUTYL ALCOHOL 71-36-3	Included in waste stream: F039	N/A
METHANOL 67-56-1	Included in waste stream: F039	N/A

California Hazardous Waste Codes 561

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status
ETHYL ALCOHOL	Toxic
64-17-5	Ignitable
BUTYL ALCOHOL 71-36-3	Toxic
ZINC TETRAOXYCHROMATE	Toxic
49663-84-5	Corrosive
	Ignitable
ISOPROPYL ALCOHOL	Toxic
67-63-0	Ignitable
METHANOL	Toxic
67-56-1	Ignitable

14. TRANSPORT INFORMATION

DOT

UN-No

UN1263

Proper shipping name

Paint

Hazard class

3

Packing Group

11

Special Provisions

149, B52, IB2, T4, TP1, TP8, TP28

Description

UN1263, Paint, 3, II, RQ

Emergency Response Guide

128

Number

UN-No

TDG

UN1263

Proper shipping name

Paint

Hazard class

3

Packing Group

Description

UN1263, Paint, 3, II

MEX

UN-No

UN1263

Proper shipping name

Paint

Hazard class **Packing Group** 11

Description

UN1263, Paint, 3, II

Revision Date: 04-Nov-2021

03174YVP-1 - METAL PRETREATMENT WASH PRIMER, MIL-C-8514C, AMEND 1, HMS15-1098E REV: (F), PART A

ICAO

UN-No UN1263
Proper shipping name Paint
Hazard class 3
Packing Group II

Special Provisions A3, A72

Description UN1263, Paint, 3, II

IATA

UN-No UN1263
Hazard class 3
Packing Group II
ERG Code 3L

Special Provisions A3, A72, A192

IMDG/IMO

 UN-No
 UN1263

 Hazard class
 3

 Packing Group
 II

 EmS-No
 F-E, S-E

 Special Provisions
 163, 367

RID

UN-No UN1263
Proper shipping name Paint
Hazard class 3
Packing Group II
Classification Code F1

Description UN1263, Paint, 3, II

ADR/RID

UN-No UN1263
Proper shipping name Paint
Hazard class 3
Packing Group II
Classification Code F1
Tunnel restriction code (D/E)

 Special Provisions
 163, 640C, 650, 367

 Description
 UN1263, Paint, 3, II, (D/E)

ADR/RID-Labels 3

ADN

Proper shipping name Paint Hazard class 3
Packing Group II
Classification Code F1

Special Provisions 163, 640C, 650 Description UN1263, Paint, 3, II

Hazard Labels 3 Limited Quantity (LQ) 5 L Ventilation VE01

15. REGULATORY INFORMATION

International Inventories

TSCA Complies
DSL/NDSL Complies
EINECS/ELINCS Complies
ENCS Complies
IECSC Complies

Revision Date: 04-Nov-2021

KECLCompliesPICCSCompliesAICSComplies

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	CAS No	SARA 313 - Threshold Values %
BUTYL ALCOHOL	71-36-3	1.0
ZINC TETRAOXYCHROMATE	49663-84-5	0.1 1.0
ISOPROPYL ALCOHOL	67-63-0	1.0
METHANOL	67-56-1	1.0

SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

CAA (Clean Air Act)

U.S. - CAA (Clean Air Act) - 1990 Hazardous Air Pollutants This product contains the following HAPs:

Chemical Name	CAS No	Hazardous air pollutants (HAPs) content
ZINC TETRAOXYCHROMATE	49663-84-5	Present
METHANOL	67-56-1	Present

Clean Water Act

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42):

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
ZINC TETRAOXYCHROMATE	N/A	×	N/A	N/A

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ (reportable quantity)
BUTYL ALCOHOL	5000 lb	N/A	RQ 5000 lb final RQ RQ 2270 kg final RQ
METHANOL	5000 lb	N/A	RQ 5000 lb final RQ RQ 2270 kg final RQ

State Regulations

Revision Date: 04-Nov-2021

California Proposition 65

This product contains the following Proposition 65 chemicals

Chemical Name	CAS No	California Proposition 65
ETHYL ALCOHOL	64-17-5	Carcinogen
		Developmental
ZINC TETRAOXYCHROMATE	49663-84-5	Carcinogen
		Developmental
		Female Reproductive
		Male Reproductive
METHANOL	67-56-1	Developmental

U.S. State Right-to-Know Regulations

Chemical Name	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
ETHYL ALCOHOL	X	X	X	X	N/A
BUTYL ALCOHOL	X	X	X	N/A	N/A
ZINC TETRAOXYCHROMATE	N/A	Х	X	Х	N/A
ISOPROPYL ALCOHOL	X	X	X	N/A	N/A
METHANOL	X	X	X	X	N/A

International Regulations

Mexico - Grade

Serious risk, Grade 3

Chemical Name	Carcinogenic Status	Exposure Limits
ETHYL ALCOHOL	A3	Mexico: STEL 1000 ppm
BUTYL ALCOHOL	N/A	Mexico: TWA 20 ppm
ZINC TETRAOXYCHROMATE	A1	Mexico: TWA 0.01 mg/m ³
ISOPROPYL ALCOHOL	N/A	Mexico: TWA 200 ppm Mexico: STEL 400 ppm
METHANOL	N/A	Mexico: TWA 200 ppm Mexico: STEL 250 ppm

16. OTHER INFORMATION

NFPA

Health Hazard 2

Flammability 3

Instability 0

Physical and Chemical Hazards -

NFPA Rating



HMIS

Health Hazard 2 * Flammability 3 Physical Hazard 0 Personal protection X

Chronic Hazard Star Legend

* Chronic Health Hazard

Issuing Date: **Revision Date:**

04-Nov-2021 04-Nov-2021

Revision Note

Revision Date: 04-Nov-2021

No information available

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

end