

SAFETY DATA SHEET

F93-Series 12610256

Section 1. Identification

Product name : F93 Series - Lusterless 85285
ML-PRF-85285E, Type I, Class H, Lusterless Polyurethane (Component A) All Colors.

Product code : F93-Series 12610256

Other means of identification : Not available.

Product type : Liquid.

Relevant identified uses of the substance or mixture and uses advised against
Paint or paint related material.

Manufacturer : THE SHERWIN-WILLIAMS COMPANY
101 W. Prospect Avenue
Cleveland, OH 44115

Emergency telephone number of the company : US/CA: (216) 566-2917
Mexico: CHEMTREC Mexico 01-800-681-9531. Available 24 hours and 365 days per year

Product information : US/Canada: Not Available
Mexico: Not Available

Telephone Number : US/Canada: (216) 566-2902
Mexico: Not Available

Regulatory information : US / Canada: (609) 424-9300
Mexico: SEIO 01-800-00-214-00 / (+52) 55-5559-1588. Available 24 hours and 365 days per year

Section 2. Hazards Identification

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture : **FLAMMABLE LIQUIDS - Category 3**
ACUTE TOXICITY (Inhalation) - Category 4
SKIN SENSITIZATION - Category 1
CARCINOGENICITY - Category 2
TOXIC TO REPRODUCTION (Fertility) - Category 1B
TOXIC TO REPRODUCTION (Unborn child) - Category 1B
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2
Percentage of the mixture consisting of ingredient(s) of unknown oral toxicity: 13.6%
Percentage of the mixture consisting of ingredient(s) of unknown dermal toxicity: 46.2%
Percentage of the mixture consisting of ingredient(s) of unknown inhalation toxicity: 10.3%

GHS label elements

Hazard pictograms :



Signal word : Danger

Date of issue/Date of revision : 11/26/2018 **Date of previous issue** : No previous validation **Version** : 1 **2/16**
F93-Series **F93 Series - Lusterless 85285**
12610256 **ML-PRF-85285E, Type I, Class H, Lusterless Polyurethane (Component A) All Colors**
6100-85-85A-093-413

Section 3. Composition/Information on Ingredients

Any concentration shown as a range is to protect confidentiality or is due to batch variation. There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.

Inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Skin contact : Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Ingestion : Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. If necessary, call a poison center or physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact : No known significant effects or critical hazards.

Inhalation : Harmful if inhaled. Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness. May cause respiratory irritation.

Skin contact : May cause an allergic skin reaction.

Ingestion : Can cause central nervous system (CNS) depression

Over-exposure signs/symptoms

Eye contact : No specific data.

Inhalation : Adverse symptoms may include the following:
respiratory tract irritation
coughing
nausea or vomiting
headache
drowsiness/fatigue
dizziness/vertigo
unconsciousness
reduced fetal weight
increase in fetal deaths
skeletal malformations

Date of issue/Date of revision : 11/26/2018 **Date of previous issue** : No previous validation **Version** : 1 **2/16**
F93-Series **F93 Series - Lusterless 85285**
12610256 **ML-PRF-85285E, Type I, Class H, Lusterless Polyurethane (Component A) All Colors**
6100-85-85A-093-413

Section 2. Hazards Identification

Hazard statements : Flammable liquid and vapor.
Harmful if inhaled.
May cause an allergic skin reaction.
May damage fertility or the unborn child.
Suspected of causing cancer.
May cause respiratory irritation.
May cause drowsiness or dizziness.
May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

Prevention : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves. Wear eye or face protection. Wear protective clothing. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical, ventilating, lighting and other equipment. Use only non-sparking tools. Use only outdoors or in a well-ventilated area. Do not breathe vapor. Contaminated work clothing must not be allowed out of the workplace.

Response : Get medical attention if you feel unwell. If exposed or concerned. Get medical attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. IF ON SKIN: Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get medical attention.

Storage : Store locked up. Store in a well-ventilated place. Keep cool.

Disposal : Dispose of contents and container in accordance with all local, regional, national and international regulations.

Supplemental label elements : **DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE**. Contains solvents which can cause permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. **WARNING**: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. **FOR INDUSTRIAL USE ONLY**. This product must be mixed with other components before use. Before opening the packages, READ AND FOLLOW WARNING LABELS ON ALL COMPONENTS.

This product contains a Significant New Use Rule (SNUR) Chemical. Do not allow this product to enter drains, sewers, wastewater treatment systems, groundwater, streams, lakes or ponds. See Environmental Data Sheet (EDS) for additional details.

Please refer to the SDS for additional information. Keep out of reach of children. Do not transfer contents to other containers for storage.

Hazards not otherwise classified : None known.

Section 3. Composition/Information on Ingredients

Substance/mixture : Mixture

Other means of identification : Not available.

CAS number/Other identifiers

Ingredient name	% by weight	CAS number
Methyl n-Amyl Ketone	210 - 627	110-43-0
Inert	210 - 625	13463-67-7
Thiolum Dioxide	210 - 625	7631-86-9
Amorphous Silica	25.6	98-06-6
p-Chlorobenzothioate	64.3	123-64-6
2,4-Pentanedione	61	1333-86-4
Carbon Black	<1	1333-20-7
Unsaturated Fatty Acids	<1	77-69-7
Xylene mixed isomers	60.3	100-41-4
Dibutyl Tartrate	60.3	
Ethylbenzene		

Date of issue/Date of revision : 11/26/2018 **Date of previous issue** : No previous validation **Version** : 1 **2/16**
F93-Series **F93 Series - Lusterless 85285**
12610256 **ML-PRF-85285E, Type I, Class H, Lusterless Polyurethane (Component A) All Colors**
6100-85-85A-093-413

Section 4. First aid measures

Skin contact : Adverse symptoms may include the following:
redness
reduced fetal weight
increase in fetal deaths
skeletal malformations

Ingestion : Adverse symptoms may include the following:
reduced fetal weight
increase in fetal deaths
skeletal malformations

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : A case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Specific treatments : No specific treatment.

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media : Use dry chemical, CO₂, water spray (fog) or foam.

Unsuitable extinguishing media : Do not use water jet.

Specific hazards arising from the chemical

Flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. The vapors are heavier than air and will spread along the ground. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back.

Hazardous thermal decomposition products

Decomposition products may include the following materials:
carbon dioxide
carbon monoxide
halogenated compounds
carbonyl halides
metal oxides

Special protective actions for fire-fighters

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal protection, protective equipment and emergency procedures

For non-emergency personnel : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

Date of issue/Date of revision : 11/26/2018 **Date of previous issue** : No previous validation **Version** : 1 **2/16**
F93-Series **F93 Series - Lusterless 85285**
12610256 **ML-PRF-85285E, Type I, Class H, Lusterless Polyurethane (Component A) All Colors**
6100-85-85A-093-413

Section 6. Accidental release measures

For emergency responders : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions : This product contains a Significant New Use Rule (SNUR) Chemical. Do not allow this product to enter drains, sewers, wastewater treatment systems, groundwater, streams, lakes or ponds. See Environmental Data Sheet (EDS) for additional details.
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and clean-up

Small spill : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities : Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Date of issue/Date of revision : 11/23/2018 Date of previous issue : No previous validation Version : 1 6/16
PDS-00000 12610236 PDS Name - Lustronix 6236 16-PPH-62362, Type 1 (Class H, Lustronix Polyurethane Component A) 48 Sales 6200-05-0A-013-113

Section 8. Exposure controls/personal protection

Occupational exposure limits (Canada)

Ingredient name	Exposure limits
Methyl n-Amyl Ketone	CA Alberta Provincial (Canada, 4/2009). 8 hrs OEL: 233 mg/m ³ 8 hours. 8 hrs OEL: 50 ppm 8 hours. CA British Columbia Provincial (Canada, 6/2017). TWA: 50 ppm 8 hours. CA Ontario Provincial (Canada, 7/2015). TWA: 25 ppm 8 hours. TWA: 115 mg/m ³ 8 hours. CA Quebec Provincial (Canada, 1/2014). TWA: 50 ppm 8 hours. TWA: 233 mg/m ³ 8 hours. CA Saskatchewan Provincial (Canada, 7/2015). STEL: 60 ppm 15 minutes. TWA: 50 ppm 8 hours. CA Ontario Provincial (Canada, 7/2015). Absorbed through skin. TWA: 25 ppm 8 hours. CA Alberta Provincial (Canada, 4/2009). Absorbed through skin. 15 min OEL: 0.2 mg/m ³ , (as Sn) 15 minutes. 8 hrs OEL: 0.1 mg/m ³ , (as Sn) 8 hours. CA British Columbia Provincial (Canada, 6/2017). Absorbed through skin. TWA: 0.1 mg/m ³ , (as Sn) 8 hours. STEL: 0.2 mg/m ³ , (as Sn) 15 minutes. CA Quebec Provincial (Canada, 1/2014). Absorbed through skin. TWA: 0.1 mg/m ³ , (as Sn) 8 hours. STEL: 0.2 mg/m ³ , (as Sn) 15 minutes. CA Ontario Provincial (Canada, 7/2015). Absorbed through skin. TWA: 0.1 mg/m ³ , (as Sn) 8 hours. STEL: 0.2 mg/m ³ , (as Sn) 15 minutes. CA Saskatchewan Provincial (Canada, 7/2015). Absorbed through skin. TWA: 0.1 mg/m ³ , (as Sn) 8 hours. STEL: 0.2 mg/m ³ , (as Sn) 15 minutes. Ethylbenzene
pentane-2,4-dione	CA Alberta Provincial (Canada, 4/2009). 8 hrs OEL: 233 mg/m ³ 8 hours. 8 hrs OEL: 50 ppm 8 hours. CA British Columbia Provincial (Canada, 6/2017). TWA: 50 ppm 8 hours. CA Ontario Provincial (Canada, 7/2015). TWA: 25 ppm 8 hours. TWA: 115 mg/m ³ 8 hours. CA Quebec Provincial (Canada, 1/2014). TWA: 50 ppm 8 hours. TWA: 233 mg/m ³ 8 hours. CA Saskatchewan Provincial (Canada, 7/2015). STEL: 60 ppm 15 minutes. TWA: 50 ppm 8 hours. CA Ontario Provincial (Canada, 7/2015). Absorbed through skin. TWA: 25 ppm 8 hours. CA Alberta Provincial (Canada, 4/2009). Absorbed through skin. 15 min OEL: 0.2 mg/m ³ , (as Sn) 15 minutes. 8 hrs OEL: 0.1 mg/m ³ , (as Sn) 8 hours. CA British Columbia Provincial (Canada, 6/2017). Absorbed through skin. TWA: 0.1 mg/m ³ , (as Sn) 8 hours. STEL: 0.2 mg/m ³ , (as Sn) 15 minutes. CA Quebec Provincial (Canada, 1/2014). Absorbed through skin. TWA: 0.1 mg/m ³ , (as Sn) 8 hours. STEL: 0.2 mg/m ³ , (as Sn) 15 minutes. CA Ontario Provincial (Canada, 7/2015). Absorbed through skin. TWA: 0.1 mg/m ³ , (as Sn) 8 hours. STEL: 0.2 mg/m ³ , (as Sn) 15 minutes. CA Saskatchewan Provincial (Canada, 7/2015). Absorbed through skin. TWA: 0.1 mg/m ³ , (as Sn) 8 hours. STEL: 0.2 mg/m ³ , (as Sn) 15 minutes. Ethylbenzene
Diisobutyl Diisocyanate	CA Alberta Provincial (Canada, 4/2009). 8 hrs OEL: 233 mg/m ³ 8 hours. 8 hrs OEL: 50 ppm 8 hours. CA British Columbia Provincial (Canada, 6/2017). TWA: 50 ppm 8 hours. CA Ontario Provincial (Canada, 7/2015). TWA: 25 ppm 8 hours. TWA: 115 mg/m ³ 8 hours. CA Quebec Provincial (Canada, 1/2014). TWA: 50 ppm 8 hours. TWA: 233 mg/m ³ 8 hours. CA Saskatchewan Provincial (Canada, 7/2015). STEL: 60 ppm 15 minutes. TWA: 50 ppm 8 hours. CA Ontario Provincial (Canada, 7/2015). Absorbed through skin. TWA: 25 ppm 8 hours. CA Alberta Provincial (Canada, 4/2009). Absorbed through skin. 15 min OEL: 0.2 mg/m ³ , (as Sn) 15 minutes. 8 hrs OEL: 0.1 mg/m ³ , (as Sn) 8 hours. CA British Columbia Provincial (Canada, 6/2017). Absorbed through skin. TWA: 0.1 mg/m ³ , (as Sn) 8 hours. STEL: 0.2 mg/m ³ , (as Sn) 15 minutes. CA Quebec Provincial (Canada, 1/2014). Absorbed through skin. TWA: 0.1 mg/m ³ , (as Sn) 8 hours. STEL: 0.2 mg/m ³ , (as Sn) 15 minutes. CA Ontario Provincial (Canada, 7/2015). Absorbed through skin. TWA: 0.1 mg/m ³ , (as Sn) 8 hours. STEL: 0.2 mg/m ³ , (as Sn) 15 minutes. CA Saskatchewan Provincial (Canada, 7/2015). Absorbed through skin. TWA: 0.1 mg/m ³ , (as Sn) 8 hours. STEL: 0.2 mg/m ³ , (as Sn) 15 minutes. Ethylbenzene

Date of issue/Date of revision : 11/23/2018 Date of previous issue : No previous validation Version : 1 6/16
PDS-00000 12610236 PDS Name - Lustronix 6236 16-PPH-62362, Type 1 (Class H, Lustronix Polyurethane Component A) 48 Sales 6200-05-0A-013-113

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits (OSHA United States)

Ingredient name	Exposure limits
Methyl n-Amyl Ketone	ACGIH TLV (United States, 3/2017). TWA: 50 ppm 8 hours. TWA: 233 mg/m ³ 8 hours. NIOSH REL (United States, 10/2016). TWA: 100 ppm 10 hours. TWA: 485 mg/m ³ 10 hours. OSHA PEL (United States, 4/2018). TWA: 100 ppm 8 hours. TWA: 465 mg/m ³ 8 hours.
Titanium Dioxide	ACGIH TLV (United States, 3/2017). TWA: 10 mg/m ³ 8 hours. OSHA PEL (United States, 4/2018). TWA: 15 mg/m ³ 8 hours. Form: Total dust NIOSH REL (United States, 10/2016). TWA: 6 mg/m ³ 10 hours.
Amorphous Silica	None. ACGIH TLV (United States, 3/2017). Absorbed through skin. TWA: 25 ppm 8 hours. NIOSH REL (United States, 10/2016). TWA: 0.1 mg of PAM-100 ¹ 10 hours. OSHA PEL (United States, 4/2018). TWA: 3.5 mg/m ³ 8 hours. ACGIH TLV (United States, 3/2017). TWA: 3 mg/m ³ 8 hours. Form: Inhalable fraction
p-Chlorobenzotrifluoride	None. ACGIH TLV (United States, 3/2017). TWA: 100 ppm 8 hours. TWA: 434 mg/m ³ 8 hours. STEL: 150 ppm 15 minutes. NIOSH REL (United States, 10/2016). OSHA PEL (United States, 4/2018). TWA: 100 ppm 8 hours. TWA: 435 mg/m ³ 8 hours.
Carbon Black	ACGIH TLV (United States, 3/2017). Absorbed through skin. TWA: 0.1 mg/m ³ , (as Sn) 8 hours. STEL: 0.2 mg/m ³ , (as Sn) 15 minutes. NIOSH REL (United States, 10/2016). Absorbed through skin. TWA: 0.1 mg/m ³ , (as Sn) 10 hours. OSHA PEL (United States, 4/2018). TWA: 0.1 mg/m ³ , (as Sn) 8 hours. ACGIH TLV (United States, 3/2017). TWA: 20 ppm 8 hours. NIOSH REL (United States, 10/2016). TWA: 100 ppm 10 hours. TWA: 435 mg/m ³ 10 hours. STEL: 125 ppm 15 minutes. STEL: 543 mg/m ³ 15 minutes. OSHA PEL (United States, 4/2018). TWA: 100 ppm 8 hours. TWA: 435 mg/m ³ 8 hours.
Unsaturated Fatty Acids	None. ACGIH TLV (United States, 3/2017). TWA: 100 ppm 8 hours. TWA: 434 mg/m ³ 8 hours. STEL: 150 ppm 15 minutes. NIOSH REL (United States, 10/2016). OSHA PEL (United States, 4/2018). TWA: 100 ppm 8 hours. TWA: 435 mg/m ³ 8 hours.
Xylene mixed isomers	None. ACGIH TLV (United States, 3/2017). TWA: 100 ppm 8 hours. TWA: 434 mg/m ³ 8 hours. STEL: 150 ppm 15 minutes. NIOSH REL (United States, 10/2016). OSHA PEL (United States, 4/2018). TWA: 100 ppm 8 hours. TWA: 435 mg/m ³ 8 hours.
Diisobutyl Diisocyanate	ACGIH TLV (United States, 3/2017). Absorbed through skin. TWA: 0.1 mg/m ³ , (as Sn) 8 hours. STEL: 0.2 mg/m ³ , (as Sn) 15 minutes. NIOSH REL (United States, 10/2016). Absorbed through skin. TWA: 0.1 mg/m ³ , (as Sn) 10 hours. OSHA PEL (United States, 4/2018). TWA: 0.1 mg/m ³ , (as Sn) 8 hours. ACGIH TLV (United States, 3/2017). TWA: 20 ppm 8 hours. NIOSH REL (United States, 10/2016). TWA: 100 ppm 10 hours. TWA: 435 mg/m ³ 10 hours. STEL: 125 ppm 15 minutes. STEL: 543 mg/m ³ 15 minutes. OSHA PEL (United States, 4/2018). TWA: 100 ppm 8 hours. TWA: 435 mg/m ³ 8 hours.
Ethylbenzene	ACGIH TLV (United States, 3/2017). TWA: 20 ppm 8 hours. NIOSH REL (United States, 10/2016). TWA: 100 ppm 10 hours. TWA: 435 mg/m ³ 10 hours. STEL: 125 ppm 15 minutes. STEL: 543 mg/m ³ 15 minutes. OSHA PEL (United States, 4/2018). TWA: 100 ppm 8 hours. TWA: 435 mg/m ³ 8 hours.

Date of issue/Date of revision : 11/23/2018 Date of previous issue : No previous validation Version : 1 6/16
PDS-00000 12610236 PDS Name - Lustronix 6236 16-PPH-62362, Type 1 (Class H, Lustronix Polyurethane Component A) 48 Sales 6200-05-0A-013-113

Section 8. Exposure controls/personal protection

Occupational exposure limits (OSHA)

Ingredient name	Exposure limits
Methyl n-Amyl Ketone	NIOSH-010-STPS-2014 (Mexico, 4/2016). TWA: 50 ppm 8 hours. NIOSH-010-STPS-2014 (Mexico, 4/2016). Absorbed through skin. TWA: 25 ppm 8 hours. NIOSH-010-STPS-2014 (Mexico, 4/2016). Absorbed through skin. TWA: 0.1 mg/m ³ , (as Sn) 8 hours. STEL: 0.2 mg/m ³ , (as Sn) 15 minutes. NIOSH-010-STPS-2014 (Mexico, 4/2016). TWA: 20 ppm 8 hours.
pentane-2,4-dione	NIOSH-010-STPS-2014 (Mexico, 4/2016). TWA: 50 ppm 8 hours. NIOSH-010-STPS-2014 (Mexico, 4/2016). Absorbed through skin. TWA: 25 ppm 8 hours. NIOSH-010-STPS-2014 (Mexico, 4/2016). Absorbed through skin. TWA: 0.1 mg/m ³ , (as Sn) 8 hours. STEL: 0.2 mg/m ³ , (as Sn) 15 minutes. NIOSH-010-STPS-2014 (Mexico, 4/2016). TWA: 20 ppm 8 hours.
Diisobutyl Diisocyanate	NIOSH-010-STPS-2014 (Mexico, 4/2016). TWA: 50 ppm 8 hours. NIOSH-010-STPS-2014 (Mexico, 4/2016). Absorbed through skin. TWA: 25 ppm 8 hours. NIOSH-010-STPS-2014 (Mexico, 4/2016). Absorbed through skin. TWA: 0.1 mg/m ³ , (as Sn) 8 hours. STEL: 0.2 mg/m ³ , (as Sn) 15 minutes. NIOSH-010-STPS-2014 (Mexico, 4/2016). TWA: 20 ppm 8 hours.
Ethylbenzene	NIOSH-010-STPS-2014 (Mexico, 4/2016). TWA: 50 ppm 8 hours. NIOSH-010-STPS-2014 (Mexico, 4/2016). Absorbed through skin. TWA: 25 ppm 8 hours. NIOSH-010-STPS-2014 (Mexico, 4/2016). Absorbed through skin. TWA: 0.1 mg/m ³ , (as Sn) 8 hours. STEL: 0.2 mg/m ³ , (as Sn) 15 minutes. NIOSH-010-STPS-2014 (Mexico, 4/2016). TWA: 20 ppm 8 hours.

Appropriate engineering controls : Use only with adequate ventilation. Use process enclosure, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Environmental exposure controls : This product contains a Significant New Use Rule (SNUR) Chemical. Do not allow this product to enter drains, sewers, wastewater treatment systems, groundwater, streams, lakes or ponds. See Environmental Data Sheet (EDS) for additional details.
Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eyes/face protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

Skin protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Body protection : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Date of issue/Date of revision : 11/23/2018 Date of previous issue : No previous validation Version : 1 6/16
PDS-00000 12610236 PDS Name - Lustronix 6236 16-PPH-62362, Type 1 (Class H, Lustronix Polyurethane Component A) 48 Sales 6200-05-0A-013-113

Section 8. Exposure controls/personal protection

Respiratory protection : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties

APPEARANCE

Physical state	: Liquid.
Color	: Various.
Odor	: Not available.
Odor threshold	: Not available.
pH	: Not available.
Melting point/freezing point	: Not available.
Boiling point/boiling range	: 138°C (280.4°F)
Flash point	: Closed cup: 39°C (102.2°F) (Pensky-Martens Closed Cup)
Evaporation rate	: 0.75 (butyl acetate = 1)
Flammability (solid, gas)	: Not available.
Lower and upper explosive (flammable) limits	: Lower: 0.9% Upper: 11.4%
Vapor pressure	: 0.93 kPa (7 mm Hg) [at 20°C]
Vapor density	: 3.5 (Air = 1)
Relative density	: 1.18
Solubility	: Not available.
Partition coefficient: n-octanol/water	: Not available.
Auto-ignition temperature	: Not available.
Decomposition temperature	: Not available.
Viscosity	: Kinematic (40°C (104°F)): >0.205 cm ² /s (>20.5 cSt)
Molecular weight	: Not applicable.
General product	
Heat of combustion	: 20,156 kJ/kg

Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. Do not allow vapor to accumulate in low or confined areas.
Incompatible materials	: Reactive or incompatible with the following materials: oxidizing materials
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Date of issue/Date of revision	: 11/26/2018	Date of previous issue	: No previous validation	Version	: 1	12/16
P93-Series 12610296	P93 Series- Lubrizol 6030 MSDS-00000000, Type 1 Class II Lubrizol Polyurethane (Component 1) All Colors.			6030-NA-GHS-US		

Section 11. Toxicological information

Product/Ingredient name	OSHA	MARC	NTP
Titanium Dioxide	-	2B	-
Amorphous Silica	-	3	-
Carbon Black	-	2B	-
Xylene mixed isomers	-	3	-
Ethylbenzene	-	2B	-

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (repeated exposure)

Name	Category	Route of exposure	Target organs
Methyl n-Amyl Ketone	Category 3	Not applicable.	Respiratory tract irritation and Narcotic effects
p-Chlorobenzotrifluoride	Category 3	Not applicable.	Respiratory tract irritation
2,4-Pentanedione	Category 3	Not applicable.	Respiratory tract irritation and Narcotic effects
Xylene mixed isomers	Category 3	Not applicable.	Respiratory tract irritation
Dibutyltin Dilaurate	Category 1	Not determined	Not determined
Ethylbenzene	Category 3	Not applicable.	Respiratory tract irritation and Narcotic effects

Specific target organ toxicity (single exposure)

Name	Category	Route of exposure	Target organs
Methyl n-Amyl Ketone	Category 2	Not determined	Not determined
2,4-Pentanedione	Category 2	Not determined	Not determined
Xylene mixed isomers	Category 2	Not determined	Not determined
Dibutyltin Dilaurate	Category 1	Oral	Not determined
Ethylbenzene	Category 2	Not determined	Not determined

Aspiration hazard

Name	Result
Xylene mixed isomers	ASPIRATION HAZARD - Category 1
Ethylbenzene	ASPIRATION HAZARD - Category 1

Information on the likely routes of exposure : Not available.

Potential acute health effects

Eye contact	: No known significant effects or critical hazards.
Inhalation	: Harmful if inhaled. Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness. May cause respiratory irritation.
Skin contact	: May cause an allergic skin reaction.
Ingestion	: Can cause central nervous system (CNS) depression.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : No specific data.

Date of issue/Date of revision	: 11/26/2018	Date of previous issue	: No previous validation	Version	: 1	12/16
P93-Series 12610296	P93 Series- Lubrizol 6030 MSDS-00000000, Type 1 Class II Lubrizol Polyurethane (Component 1) All Colors.			6030-NA-GHS-US		

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity	Product/Ingredient name	Result	Species	Dose	Exposure
	Methyl n-Amyl Ketone	LD50 Oral	Rat	1600 mg/kg	-
	p-Chlorobenzotrifluoride	LD50 Oral	Rat	13 g/kg	-
	2,4-Pentanedione	LD50 Oral	Rat	55 mg/kg	-
	Carbon Black	LD50 Oral	Rat	>15400 mg/kg	4 hours
	Xylene mixed isomers	LD50 Inhalation Gas.	Rat	5000 ppm	-
	Dibutyltin Dilaurate	LD50 Oral	Rat	4300 mg/kg	-
	Ethylbenzene	LD50 Oral	Rat	2071 mg/kg	-
		LD50 Dermal	Rabbit	>5000 mg/kg	-
		LD50 Oral	Rabbit	3500 mg/kg	-

Irritation/Corrosion

Product/Ingredient name	Result	Species	Score	Exposure	Observation
Methyl n-Amyl Ketone	Skin - Mild Irritant	Rabbit	-	24 hours 14 milligrams	-
Titanium Dioxide	Skin - Mild Irritant	Human	-	72 hours 300 Micrograms	-
Amorphous Silica	Eyes - Mild Irritant	Rabbit	-	24 hours 25 milligrams	-
2,4-Pentanedione	Eyes - Severe Irritant	Rabbit	-	20 milligrams	-
	Skin - Mild Irritant	Rabbit	-	48 hours 11.2 milligrams	-
	Skin - Moderate Irritant	Rabbit	-	48 hours 11.2 milligrams	-
	Skin - Moderate Irritant	Rabbit	-	6 hours 33.6 milligrams	-
Xylene mixed isomers	Eyes - Mild Irritant	Rabbit	-	24 hours 5 milligrams	-
	Eyes - Severe Irritant	Rabbit	-	8 hours 60 micrograms	-
	Skin - Mild Irritant	Rat	-	24 hours 500 milligrams	-
	Skin - Moderate Irritant	Rabbit	-	100 Percent	-
Dibutyltin Dilaurate	Skin - Moderate Irritant	Rabbit	-	24 hours 100 milligrams	-
	Eyes - Moderate Irritant	Rabbit	-	500 milligrams	-
	Skin - Severe Irritant	Rabbit	-	500 milligrams	-
Ethylbenzene	Eyes - Severe Irritant	Rabbit	-	24 hours 15 milligrams	-
	Skin - Mild Irritant	Rabbit	-		-

Sensitization

Not available.

Reproductive toxicity

Not available.

Cardiotoxicity

Not available.

Carcinogenicity

Date of issue/Date of revision	: 11/26/2018	Date of previous issue	: No previous validation	Version	: 1	12/16
P93-Series 12610296	P93 Series- Lubrizol 6030 MSDS-00000000, Type 1 Class II Lubrizol Polyurethane (Component 1) All Colors.			6030-NA-GHS-US		

Respiration

: Adverse symptoms may include the following:
respiratory tract irritation
coughing
nauseas or vomiting
headache
drowsiness/fatigue
dizziness/vertigo
unconsciousness
reduced fetal weight
increase in fetal deaths
skeletal malformations

Skin contact

: Adverse symptoms may include the following:
irritation
redness
reduced fetal weight
increase in fetal deaths
skeletal malformations

Ingestion

: Adverse symptoms may include the following:
reduced fetal weight
increase in fetal deaths
skeletal malformations

Delayed and immediate effects and also chronic effects from short and long term exposures

Short term exposures

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Long term exposures

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

General

: May cause damage to organs through prolonged or repeated exposure. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

Carcinogenicity

: Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.

Mutagenicity

: No known significant effects or critical hazards.

Teratogenicity

: May damage the unborn child.

Developmental effects

: No known significant effects or critical hazards.

Fertility effects

: May damage fertility.

Numerical measures of toxicity

Acute toxicity estimates

Route	ATE value
Oral	3389.5 mg/kg
Dermal	3734.4 mg/kg
Inhalation (gases)	13502.8 ppm
Inhalation (vapors)	20.75 mg/l

Date of issue/Date of revision	: 11/26/2018	Date of previous issue	: No previous validation	Version	: 1	12/16
P93-Series 12610296	P93 Series- Lubrizol 6030 MSDS-00000000, Type 1 Class II Lubrizol Polyurethane (Component 1) All Colors.			6030-NA-GHS-US		

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
Methyl n-Amyl Ketone	Acute LC50 131000 µg/l Fresh water	Fish - Pimephales promelas	96 hours
Titanium Dioxide	Acute LC50 >1000000 µg/l Marine water	Fish - Fundulus heteroclitus	96 hours
2,4-Pentanedione	Acute EC50 75000 µg/l Fresh water	Crustaceans - Ceriodaphnia reticulata - Larvae	48 hours
	Acute LC50 47600 µg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
Xylene mixed isomers	Acute LC50 60100 µg/l Fresh water	Fish - Lepomis macrochirus	96 hours
	Acute LC50 6500 µg/l Marine water	Crustaceans - Palaemonetes pugio	48 hours
Dibutyltin Dilaurate	Acute LC50 13400 µg/l Fresh water	Fish - Pimephales promelas	96 hours
	Chronic EC10 >2 mg/l Fresh water	Algae - Scenedesmus subspicatus	96 hours
Ethylbenzene	Acute EC50 4600 µg/l Fresh water	Algae - Pseudokirchneriella subcapitata	72 hours
	Acute EC50 3600 µg/l Fresh water	Algae - Pseudokirchneriella subcapitata	96 hours
	Acute EC50 6530 µg/l Fresh water	Crustaceans - Artemia sp. - Nauplii	48 hours
	Acute EC50 2930 µg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute LC50 4200 µg/l Fresh water	Fish - Oncorhynchus mykiss	96 hours

Persistence and degradability

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Methyl n-Amyl Ketone	-	-	Ready
Xylene mixed isomers	-	-	Ready
Ethylbenzene	-	-	Ready

Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
Xylene mixed isomers	-	8.1 to 25.9	low
Dibutyltin Dilaurate	-	2.91	low

Mobility in soil

Soil/water partition coefficient (K_{oc}) : Not available.

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods : This product contains a Significant New Use Rule (SNUR) Chemical. Do not allow this product to enter drains, sewers, wastewater treatment systems, groundwater, streams, lakes or ponds. See Environmental Data Sheet (EDS) for additional details.

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should be at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been

Date of issue/Date of revision : 11/26/2018	Date of previous issue : No previous validation	Version : 1	15/16
F93-Series 12610256	F93 Series - Lactidex 83263 MS-PP-44-2555, Type 1 Class H, Lactidex Polyurethane (Component A) All Colors	BMH-45-AU-GHS-US	

Section 14. Transport information

Ship type : Not available.
Pollution category : Not available.

Section 15. Regulatory information

U.S. Federal regulations : TSCA §(p)2 final significant new use rules: 2,4-Pentanedione

This product contains a Significant New Use Rule (SNUR) Chemical. Do not allow this product to enter drains, sewers, wastewater treatment systems, groundwater, streams, lakes or ponds. See Environmental Data Sheet (EDS) for additional details.

SARA 313

SARA 313 (40 CFR 372.45) supplier notification can be found on the Environmental Data Sheet.

California Prop. 65

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

International regulations

International lists : Australia Inventory (AICS): Not determined.
China Inventory (CECSC): Not determined.
Japan Inventory (JENCS): Not determined.
Japan Inventory (JSHL): Not determined.
Korea Inventory (KECI): Not determined.
Malaysia Inventory (EHS Register): Not determined.
New Zealand Inventory of Chemicals (NZIoC): Not determined.
Philippines Inventory (PICCS): Not determined.
Taiwan Chemical Substances Inventory (TCSI): Not determined.
Thailand Inventory: Not determined.
Turkey Inventory: Not determined.
Vietnam Inventory: Not determined.

Section 16. Other information

Hazardous Material Information System (U.S.A.)

Health	3
Flammability	2
Physical hazards	0

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

Procedure used to derive the classification

Classification	Justification
FLAMMABLE LIQUIDS - Category 3	On basis of test data
ACUTE TOXICITY (inhalation) - Category 4	Calculation method
SKIN SENSITIZATION - Category 1	Calculation method
CARCINOGENICITY - Category 2	Calculation method
TOXIC TO REPRODUCTION (Fertility) - Category 1B	Calculation method
TOXIC TO REPRODUCTION (Unborn child) - Category 1B	Calculation method
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3	Calculation method
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3	Calculation method
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2	Calculation method

Date of issue/Date of revision : 11/26/2018	Date of previous issue : No previous validation	Version : 1	15/16
F93-Series 12610256	F93 Series - Lactidex 83263 MS-PP-44-2555, Type 1 Class H, Lactidex Polyurethane (Component A) All Colors	BMH-45-AU-GHS-US	

Section 13. Disposal considerations

cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	DOT Classification	TDG Classification	Mexico Classification	IATA	IMDG
UN number	UN1263	UN1263	UN1263	UN1263	UN1263
UN proper shipping name	PAINT	PAINT	PAINT	PAINT	PAINT
Transport hazard class(es)	3	3	3	3	3
Packing group	III	III	III	III	III
Environmental hazards	No.	No.	No.	No.	No.
Additional information	This product may be re-classified as "Combustible Liquid," unless transported by vessel or aircraft. Non-bulk packages (less than or equal to 118 gal) of combustible liquids are not regulated as hazardous materials in package sizes less than the product reportable quantity. ERG No. 128	Product classified as per the following sections of the Transportation of Dangerous Goods Regulations: 2, 18-2.19 (Class 3). ERG No. 128	-	-	Emergency schedule F, 6-E

Special precautions for user : Multi-modal shipping descriptions are provided for informational purposes and do not consider container sizes. The presence of a shipping description for a particular mode of transport (sea, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport. People loading and unloading dangerous goods must be trained on all of the risks deriving from the substances and on all actions in case of emergency situations.

Transport in bulk according to Annex II of MARPOL and the IBC Code : Not available.

Proper shipping name : Not available.

Date of issue/Date of revision : 11/26/2018	Date of previous issue : No previous validation	Version : 1	15/16
F93-Series 12610256	F93 Series - Lactidex 83263 MS-PP-44-2555, Type 1 Class H, Lactidex Polyurethane (Component A) All Colors	BMH-45-AU-GHS-US	

Section 16. Other information

History

Date of printing : 11/26/2018
Date of issue/Date of revision : 11/26/2018
Date of previous issue : No previous validation
Version : 1
Key to abbreviations : ATE = Acute Toxicity Estimate
BCF = Bioconcentration Factor
GHS = Globally Harmonized System of Classification and Labeling of Chemicals
IATA = International Air Transport Association
IBC = Intermediate Bulk Container
IMDG = International Maritime Dangerous Goods
LogPow = logarithm of the octanol/water partition coefficient
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpo" = marine pollution)
UN = United Nations

Notice to reader

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by the manufacturer, including but not limited to the incorporation of products not specified by the manufacturer, or the use or addition of products in proportions not specified by the manufacturer. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.

Date of issue/Date of revision : 11/26/2018	Date of previous issue : No previous validation	Version : 1	15/16
F93-Series 12610256	F93 Series - Lactidex 83263 MS-PP-44-2555, Type 1 Class H, Lactidex Polyurethane (Component A) All Colors	BMH-45-AU-GHS-US	