

Stock Number: 3142045 **Revision Date:** 10-26-2023 **Replaces:** 04-05-2021

BLACK BEAR PAR-AL-KETONE

1. Identification

Product identifier used on the label: **PAR-AL-KETONE**

Stock Number: 3142045

PARALKETONE5, PARALKETONE16, PARALKETONE55, Other means of identification:

PARALKETONEQT, PARALKETONEGL Synonyms:

Chemical family: Mixture

Recommended use of the chemical and restrictions on use:

Recommended use: Corrosion Preventive Compound

Restrictions on use: Uses other than those described above

Name, address, and telephone number

of the chemical manufacturer,

Daubert Chemical Company

importer, or other responsible party:

4700 S. Central Avenue

Chicago, IL 60638

1-708-496-7350

Telephone number: E-mail address: SDS@Daubert.com

Emergency phone number: Chemtrec: 1-800-424-9300 (International)

2. Hazard(s) identification

Classification of the chemical in accordance with paragraph (d) of §1910.1200:

GHS Hazard Symbols:





GHS Classification: Skin Corrosion/Irritation Category 2; Flammable Liquid Category 3; Specific

Target Organ Systemic Toxicity (STOT) - Single Exposure Category

Signal Word: Warning

Hazard Statements: Flammable liquid and vapor

Causes skin irritation

May cause drowsiness or dizziness

Unclassified Hazards (HNOC):: None Identified

Precautionary Statements:

Prevention: Keep away from heat/sparks/open flames/hot surfaces. – No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting equipment.

Use only non-sparking tools.



Product identifier used on the label: PAR-AL-KETONE

Stock Number: 3142045 Revision Date: 10-26-2023 Replaces: 04-05-2021

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/ vapors/spray.

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face

protection.

Response: If on skin: Wash with plenty of water.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse

skin with water/shower.

If inhaled: Remove person to fresh air and keep comfortable for

breathing.

Call a poison center/doctor if you feel unwell.

Specific treatment: see Section 4 on this SDS.

If skin irritation occurs: Get medical advice/attention.

Take off contaminated clothing and wash it before reuse.

In case of fire: Use appropriate media to extinguish.

Storage: Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Disposal: Dispose of contents/container to a suitable disposal site in accordance

with local/national/international regulations.

Hazards not otherwise classified:No data available

3. Composition/information on ingredients

Chemical Name	Common name and synonyms	CAS#	%
Hydrotreated light distillate (Petroleum)	None	64742-47-8	30 - 60
Sulfonic Acids, Petroleum , Sodium Salts	None	68608-26-4	1 - 5

Specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.



Product identifier used on the label: PAR-AL-KETONE

Stock Number: 3142045 Revision Date: 10-26-2023 Replaces: 04-05-2021

4. First-aid measures

Description of necessary measures, subdivided according to the different routes of exposure, i.e., inhalation, skin and eye contact, and ingestion:

Inhalation: If symptoms are experienced remove source of contamination or move

victim to fresh air and obtain medical advice.

Eye Contact: Immediately flush eyes with plenty of water for at least 20 minutes

retracting eyelids often. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Get immediate medical attention and monitor the eye daily as advised by your physician.

Skin Contact: Wash with soap and water. Remove contaminated clothing and launder.

Get medical attention if irritation develops or persists.

Ingestion: Do not induce vomiting and seek medical attention immediately. Provide

medical care provider with this SDS. If vomiting occurs, lean victim

forward to reduce risk of aspiration into lungs.

Most important symptoms/effects,

acute and delayed:

Causes skin irritation. May cause drowsiness or dizziness

Indication of immediate medical attention and special treatment

needed, if necessary:

Consult a physician. Treat symptomatically.

5. Fire-fighting measures

Suitable (and unsuitable) extinguishing media:

Suitable extinguishing media: Use alcohol resistant foam, carbon dioxide, dry chemical, or water spray

when fighting fires. Water or foam may cause frothing if liquid is burning but it still may be a useful extinguishing agent if carefully applied to the

fire.

Unsuitable extinguishing media: Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the

chemical:

Vapors may be ignited by sparks, flames or other sources of ignition if material is above the flash point giving rise to a fire (Class B). Vapors are heavier than air and may travel to a source of ignition and flash back. Empty containers that retain product residue (liquid, solid/sludge, or vapor) can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose container to heat, flame, sparks, static electricity, or other sources of ignition. Any of these actions can potentially cause an

explosion that may lead to injury or death.

Hazardous combustion products: Carbon dioxide, Carbon monoxide, Hydrocarbons



Product identifier used on the label: PAR-AL-KETONE

Stock Number: 3142045 Revision Date: 10-26-2023 Replaces: 04-05-2021

Special protective equipment and precautions for fire-fighters:

Do not enter fire area without proper protection including self-contained breathing apparatus and full protective equipment. Fight fire from a safe distance and a protected location due to the potential of hazardous vapors and decomposition products.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures:

Exposure to the spilled material may be irritating or harmful. Follow personal protective equipment recommendations found in Section 8 of this SDS. Additional precautions may be necessary based on special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred. Also consider the expertise of employees in the area responding to the spill.

Methods and materials for containment and cleaning up:

Absorb or cover with dry earth, sand or other non-combustible material and transfer to appropriate waste containers. Use clean, non-sparking tools to collect absorbed material. Collect and discard in accordance with local, state and national regulations.

7. Handling and storage

Precautions for safe handling:

Avoid contacting and avoid breathing the material. Use only in a well ventilated area. "Empty" containers retain product residue (liquid and/or vapor) and can be dangerous. Ground and bond containers when transferring material. Do not get in eyes, on skin and clothing. Wash thoroughly after handling. As with all chemicals, good industrial hygiene practices should be followed when handling this material.

Conditions for safe storage, including any incompatibilities:

Safe storage conditions:

Store in a cool dry ventilated location. Isolate from incompatible materials and conditions. Keep container(s) closed. Do not store in direct

sunlight Keep away from heat, sparks, and flame.

Materials to Avoid/Chemical

Incompatibility:

Strong oxidizing agents

8. Exposure controls/personal protection

OSHA permissible exposure limit (PEL), American Conference of Governmental Industrial Hygienists (ACGIH) Threshold Limit Value (TLV), and any other exposure limit used or recommended by the chemical manufacturer, importer, or employer preparing the safety data sheet, where available:

Chemical component	OSHA PEL	ACGIH TLV	ACGIH STEL	IDLH
Hydrotreated light		200 mg/m3	No data available	No data available
distillate (Petroleum)				



Product identifier used on the label: PAR-AL-KETONE

Stock Number: 3142045 Revision Date: 10-26-2023 Replaces: 04-05-2021

Appropriate engineering controls:

Local exhaust ventilation or other engineering controls are normally required when handling or using this product to avoid overexposure.

Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits

Engineering controls must be designed to meet the OSHA chemical

specific standard in 29 CFR 1910.

Individual protection measures, such as personal protective equipment:

Respiratory Protection: Proper ventilation (at a minimum) will be required when handling this

product. Use respirators (NIOSH approved) only if ventilation cannot be used to eliminate symptoms or reduce the exposure to below acceptable levels. Follow a respiratory protection program that meets 29 CFR 1910.134 and ANSI Z88.2 requirements whenever work place conditions

warrant the use of a respirator.

Respirator Type(s): NIOSH approved air purifying respirator with organic vapor cartridge.

Eye protection: Wear chemically resistant safety glasses with side shields when handling

this product. Wear additional eye protection such as chemical splash goggles and/or face shield when the possibility exists for eye contact with splashing or spraying liquid, or airborne material. Do not wear contact

lenses. Have an eye wash station available.

Skin protection: Wear protective gloves. Inspect gloves for chemical break-through and

replace at regular intervals. Clean protective equipment regularly. Wash hands and other exposed areas with mild soap and water before eating,

drinking, and when leaving work.

Gloves: Chemically resistant gloves

Other protective equipment: Wear chemically resistant safety glasses with side shields when handling

this product. Wear additional eye protection such as chemical splash goggles and/or face shield when the possibility exists for eye contact with splashing or spraying liquid, or airborne material. Do not wear contact

lenses. Have an eye wash station available.

Wear protective gloves. Inspect gloves for chemical break-through and replace at regular intervals. Clean protective equipment regularly. Wash hands and other exposed areas with mild soap and water before eating,

drinking, and when leaving work.

General hygiene conditions: "Empty" containers retain product residue (liquid and/or vapor) and can

be dangerous. Ground and bond containers when transferring material. Do not get in eyes, on skin and clothing. Wash thoroughly after handling.

As with all chemicals, good industrial hygiene practices should be

followed when handling this material.

BLACK BEAR

Safety Data Sheet

Product identifier used on the label: PAR-AL-KETONE

Stock Number: 3142045 Revision Date: 10-26-2023 Replaces: 04-05-2021

9. Physical and chemical properties

Appearance (physical state, color etc.):

Physical state: Liquid
Color: Amber

Odor: Solvent Odor

Slight

Odor Threshold: No data available pH: No data available

Melting point/freezing point (°C):

 $\begin{tabular}{lll} \begin{tabular}{lll} \begin{$

Upper/lower flammability or explosive

limits:

Upper flammability or explosive limits: No data available
Lower flammability or explosive limits: No data available
Vapor pressure: 2 mmHg @ 20°C
Vapor density: >1 (Air=1)
Relative density: 0.86

Solubility(ies):

Partition coefficient: n-octanol/water:

Auto-ignition temperature (°C):

No data available

Volatiles, % by weight: 44.8
VOC, Material, lb/gal 3.22
VOC, Material, grams/liter 386.2
VOC minus exempt solvents & water, g/L 386



Product identifier used on the label: PAR-AL-KETONE

Stock Number: 3142045 Revision Date: 10-26-2023 Replaces: 04-05-2021

10. Stability and reactivity

Reactivity: Not expected to be reactive

Chemical stability: Hazardous polymerization will not occur.

Possibility of hazardous reactions: Under normal conditions of storage and use, hazardous reactions will not

occur.

Conditions to avoid (e.g., static discharge, shock, or vibration):

Temperatures above flash point in combination with sparks, open flames, or other sources of ignition. Elevated temperatures. Contamination.

Incompatible materials: Strong oxidizing agents

Hazardous decomposition products: Under normal conditions of use & storage, decomposition and hazardous

decomposition products are unlikely.

11. Toxicological information

Description of the various toxicological (health) effects and the available data used to identify those effects:

Information on the likely routes of exposure (inhalation, ingestion, skin

and eye contact):

Eye contact, Skin contact, Inhalation

Symptoms related to the physical,

chemical and toxicological

characteristics:

Causes skin irritation. . May cause drowsiness or dizziness

Delayed and immediate effects and also chronic effects from short- and long-term exposure:

Ingestion Toxicity: Harmful if swallowed.

Skin Contact: Can cause moderate skin irritation, defatting, and dermatitis. Not likely to

cause permanent damage.

Inhalation Toxicity: No data available

Eye Contact: Contact with the eyes may cause moderate to severe eye injury. Eye

contact may result in tearing and reddening, but not likely to

permanently injure eye tissue. Temporary vision impairment (cloudy or

blurred vision) is possible.

Sensitization: None known

Mutagenicity: No data

Reproductive and Developmental

No data available

Toxicity:

Carcinogenicity: There are no carcinogenic ingredients present at or over 0.1%.



Product identifier used on the label: PAR-AL-KETONE

Stock Number: 3142045 Revision Date: 10-26-2023 Replaces: 04-05-2021

STOT-single exposure: Classification has been based on toxicological information of the

components in Section 3.

STOT-repeated exposure: Based on available data, the classification criteria are not met.

Aspiration hazard: Based on available data, the classification criteria are not met.

Numerical measures of toxicity (such as acute toxicity estimates):

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Hydrotreated light			Inhalation LC50 (4h) Rat >
distillate (Petroleum)			20 mg/L

Is the hazardous chemical listed in the National Toxicology Program (NTP) Report on Carcinogens (latest edition) or has it been found to be a potential carcinogen in the International Agency for Research on Cancer (IARC) Monographs (latest edition), or by OSHA?:

Chemical Name	OSHA Carcinogen	IARC Carcinogen	NTP Carcinogen
No component of this			
product present at levels			
greater than or equal to			
0.1% is identified as a			
known or anticipated			
carcinogen.			

12. Ecological information

Ecotoxicity (aquatic and terrestrial,

No data available

where available):

Ecological Toxicity Data:

Chemical Name	CAS#	Aquatic EC50 Crustacea	Aquatic ERC50 Algae	Aquatic LC50 Fish
No data available				

Persistence and degradability: No data

Bioaccumulative potential:No data availableMobility in soil:No data availableOther adverse effects (such asNo data available

hazardous to the ozone layer):



Product identifier used on the label: PAR-AL-KETONE

Stock Number: 3142045 Revision Date: 10-26-2023 Replaces: 04-05-2021

13. Disposal considerations

Description of waste residues and information on their safe handling and methods of disposal, including the disposal of any contaminated packaging:

Spent or discarded material may be a hazardous waste.

Dispose of by incineration following Federal, State, Local, or Provincial

regulations.

Waste codes / waste designations: D001

14. Transport information

Domestic Ground in containers <= 119 GL Corrosion preventive/Non-Regulated

Domestic Ground in containers > 119 GL UN1268, PETROLEUM DISTILLATES, N.O.S.,(Naphtha Solvent),

Combustible liquid, PG III

Shipping name for Export, Air (IATA) UN1268, PETROLEUM DISTILLATES, N.O.S., (Naphtha Solvent), 3, PG

Ш

Shipping name for Export, Sea (IMDG) UN1268, PETROLEUM DISTILLATES, N.O.S., (Naphtha Solvent), 3, PG

Ш

Marine Pollutant? No

STATUS

15. Regulatory information

LIST

Status of formula components on selected national regulatory inventories:

TSCA All components in this product are on the TSCA Inventory or exempt.

Canadian DSL One or more chemical substances in this material are on the Canadian NDSL and

the remainder are included on the Canadian DSL or are exempt.

Chemical Name CAS # Regulation Percent

Naphthalene 91-20-3 Prop. 65 - Cancer TRACE



Product identifier used on the label: PAR-AL-KETONE

Stock Number: 3142045 Revision Date: 10-26-2023 Replaces: 04-05-2021

and an	nepiaces. (04-05-2021	
Cumene	98-82-8	Prop. 65 - Cancer	TRACE
Benzene	71-43-2	Prop. 65 - Cancer	TRACE
Ethylbenzene	100-41-4	Prop. 65 - Cancer	TRACE
Toluene	108-88-3	Prop. 65 - Developmental and/or Reproductive	<0.1
Benzene	71-43-2	Prop. 65 - Developmental and/or Reproductive	TRACE
Toluene	108-88-3	CERCLA	<0.1
			RQ = 1000 lbs
Naphthalene	91-20-3	CERCLA	TRACE
			RQ = 100 lbs.
Cumene	98-82-8	CERCLA	TRACE
			RQ = 5000 lbs.
Benzene	71-43-2	CERCLA	TRACE
			RQ = 10 lbs.
Ethylbenzene	100-41-4	CERCLA	TRACE
			RQ = 1000 lbs.
Toluene	108-88-3	SARA 313	<0.1
Cumene	98-82-8	SARA 313	TRACE
Naphthalene	91-20-3	SARA 313	TRACE
Benzene	71-43-2	SARA 313	TRACE
Ethylbenzene	100-41-4	SARA 313	TRACE
No SARA 302 EHS-listed chemicals in this product.		SARA EHS	



Product identifier used on the label: PAR-AL-KETONE

Stock Number: 3142045 Revision Date: 10-26-2023 Replaces: 04-05-2021

16. Other information, including date of preparation or last revision.

SDS Prepared by:Black Bear Lubricants Inc.

Revision Date: 10-26-2023

Revision Number: 3

Reason for revision: Reviewed

Approved By: S. Clyne

Disclaimer: Although the information contained herein is believed to be reliable, it is

furnished without warranty of any kind. This information is not intended to be all-inclusive as to the manner and conditions of use, handling, and

storage.